

SOLAR POWER STATION SELECTION GUIDE



FACTORS TO CONSIDER:		
Load	How much power the devices you wish to operate draw	
Solar Radiation	How much sunlight is available in your location	






This guide shows the maximum continuous power in watts that each of OutBack's five SPS units can provide for a given location based on seasonal variation of solar resource. Note that this is continuous operation—if the load you are powering is not constantly on you can use a higher-power consumption device.

If you need more wattage than a given system can provide on a continuous basis, look to the larger systems until you find one that can deliver the power you need for that given location based on the solar energy available. If you are in an area receiving less sunlight, make sure you observe the power rating guidelines to the right of the map. Also note that system performance is affected by panel orientation, any shading present, and ambient temperature.


SPS.SYS.1.106.12






Load	
Maximum Supported Continuous Load**:	24W
Maximum 3-Day Blackout Autonomy:	9W


SPS.SYS.2.156.24






Load	
Maximum Supported Continuous Load**:	56W
Maximum 3-Day Blackout Autonomy:	22W


SPS.SYS.2.318.24






Load	
Maximum Supported Continuous Load**:	65W
Maximum 3-Day Blackout Autonomy:	55W


SPS.SYS.3.318.24






Load	
Maximum Supported Continuous Load**:	85W
Maximum 3-Day Blackout Autonomy:	55W

SPS.SYS.3.200.48





Load	
Maximum Supported Continuous Load**:	95W
Maximum 3-Day Blackout Autonomy:	70W