




## THE MM-E SERIES INVERTER/CHARGER



Modified  
Sine  
Wave



12, 24

Battery  
Voltage  
Options



1000-  
1300 VA

Continuous  
Output  
Options

Sensata Technologies now offers the MM-E Series Inverter/Charger for 230 VAC / 50 Hz installations. The MM-E Series comes with all of the features you've come to expect from a Magnum Energy brand product, including:

**Power Factor Corrected (PFC) Charger:** Our PFC charger is built into all of our inverter chargers. It uses less energy from a generator than a standard charger – using 25-30% less AC current than standard chargers.

**Battery temp sensor:** The standard battery temp sensor monitors temperatures from 0 - 50° C.

**Convenient switches:** All models come with an on/off inverter-mounted switch with an easy-to-read LED indicator.

### Model Numbers

- MM1012E
- MM1324E

### Available For

- Renewable Energy Systems  
Off-grid Power  
Back-up Power

### Available Accessories

- Battery Monitor Kit
- Fuse Blocks
- Remotes - MM-RC/ME-RC

## FEATURES

### Attractive styling:

The modern, hourglass case, paired with the die cast aluminum base combines form with function, creating an attractive unit that uses its base as a heat sink for superior high temperature operation.

### Fan cooled:

The MM-E Series is fan cooled, enabling the unit to work well in confined spaces. If the inverter does exceed its temperature limits, it will automatically shut down and then restart when it cools down.

### Versatile mounting:

Mount the MM-E Series on a shelf, wall, or even upside down.

### Battery and inverter protection:

The MM-E Series protects your batteries and itself with low battery, high battery, current overload, and circuit breaker protection.

# MM-E SERIES INVERTER/CHARGER SPECIFICATIONS

	MM1012E	MM1324E
INVERTER SPECIFICATIONS		
Input battery voltage range	9 - 16 VDC	18 - 32 VDC
Nominal AC output voltage	230 VAC ± 5%	230 VAC ± 5%
Output frequency and accuracy	50 Hz ± 0.4 Hz	50 Hz ± 0.4 Hz
1 msec surge current (amps AC)	21	42
100 msec surge current (amps AC)	11	14
5 sec surge power (real watts)	1750	2600
30 sec surge power (real watts)	1600	2100
5 min surge power (real watts)	1350	1850
30 min surge power (real watts)	1180	1650
Continuous power output at 25° C	1000 VA	1300 VA
Maximum continuous input current	133 ADC	87 ADC
Inverter efficiency (peak)	87%	87%
Transfer time	30 ms	30 ms
Search mode (typical)	< 6 watts	< 8 watts
No load (120 VAC output, typical)	16 watts	18 watts
Waveform	Modified Sine Wave	Modified Sine Wave
CHARGER SPECIFICATIONS		
Continuous output at 25° C	50 A	40 A
Charger efficiency	84%	83%
Power factor	> .95	> .95
Input current at rated output (AC amps)	3.5	5.5
GENERAL FEATURES AND CAPABILITIES		
Transfer relay capability	20 AAC	
Five stage charging capability	Bulk, Absorb, Float, Equalize (requires remote), and Battery Saver™	
Battery temperature compensation	Yes, 15 ft Battery Temp Sensor standard	
Internal cooling	0 to 59 cfm variable speed	
Overcurrent protection	Yes, with two overlapping circuits	
Overtemperature protection	Yes on transformer, MOSFETS, and battery	
Corrosion protection	Yes, PCB's conformal coated, powder coated chassis/top, and stainless steel fasteners	
Low battery cutoff	10 VDC, adjustable with the ME-RC remote	
Output circuit breaker	7 AAC	
Input circuit breaker	8 AAC	
Listings	None	
Warranty	Two years	
ENVIRONMENTAL SPECIFICATIONS		
Temperature (Operating/Non-operating)	-20° C to +60° C (-4° F to 140° F) to -40° C to +70° C (-40° F to 158° F)	
Operating humidity	0 to 95% RH non-condensing	
PHYSICAL SPECIFICATIONS		
Dimensions (l x w x h)	15.0" x 6.5" x 5.0" (38.1 cm x 16.5 cm x 12.7 cm)	
Mounting	Shelf (top or bottom up) or wall	
Weight	23 lb (10.4 kg)	
Shipping weight	24 lb (10.9 kg)	
Max operating altitude	15,000' (4570 m)	



## OFFICES

2211 West Casino Road  
Everett, Washington 98204 USA  
425-353-8833

4467 White Bear Pkwy  
St. Paul, MN 55110 USA  
800-553-6418