



NKCR.E146236 Auxiliary Devices

[Page Bottom](#)

Auxiliary Devices

[See General Information for Auxiliary Devices](#)

IMO PRECISION CONTROLS LTD

E146236

1000 N Circular Rd
Staples Corner
London, NW2 7JP UNITED KINGDOM

Investigated to ANSI/UL 508

Auxiliary Device Enclosed Model(s) LG, followed by MSx, followed by 5 alphanumeric digits, may be followed by any alphanumeric digits.

Auxiliary Device Open type Suppressor Units Model(s) RC-MCN@, RC-MCNW@

Auxiliary contact blocks Model(s) A69-01, A69-10, A69-11, A69-11X, HK Series, McA...., MCAH...., MCAS-01, MCAS-10, MCAS-11, MCAS-11X

Auxiliary devices Model(s) MC-DK, MC-IN..., MC-SK, MC-UN....

MCR07, followed by A or D, followed by 0, 1, 2, 3 or 4 followed by 0, 1, 2, 3 or 4.

MCR07N-S, followed by 0, 1, 2, 3, or 4 followed by 0, 1, 2, 3, or 4.

MCRD07-S, followed by A or D, followed by 0, 1, 2, 3 or 4, followed by 0, 1, 2, 3 or 4.

Contact blocks, "Series VF B" Model(s) VF B10*, VF B11*, VF B13*, VF B14*, VF B15*, VF B16*, VF B17*, VF B18*, VF B2*, VF B20*, VF B21*, VF B22*, VF B28*, VF B29*, VF B3*, VF B30*, VF B33*, VF B34*, VF B5*, VF B6*, VF B7*, VF B8*, VF B9*

Contact blocks, "Series VF M" Model(s) VF M4*, VF M4B*, VF M4C*

Contact blocks Model(s) VF M6*

Control units Model(s) CS, followed by AR-, AT-, DM-, ME-, followed by two alphanumeric digits, followed by V or M, followed by 024, 120 or 230.

Latch mechanisms, "Series FA" Model(s) FA41XX*, FA45XX*, FA46XX*, FA48XX*

Latch mechanisms, "Series FB" Model(s) FB41XX*, FB45XX*, FB46XX*, FB48XX*

Latch mechanisms, "Series FF" Model(s) FF41XX*, FF45XX*, FF46XX*, FF48XX*

Latch mechanisms Model(s) FS, followed by one or two characters, followed by two characters, followed by D or E, followed by 024, 120 or 230.

MC-L....

MS, followed by six alphanumeric digits, may be followed by any alphanumeric digits.

Limit switches Model(s) FC*, FD*, FE*, FK*, FL*, FM*, FP*, FR*, FX*, FZ*, LD*, LL*, LM*, LP*, LR*, LX*, LZ*

Series MA followed by six alphanumeric digits, maybe followed by any alphanumeric digits.

Series MB followed by six alphanumeric digits, maybe followed by any alphanumeric digits.

Series PA followed by six alphanumeric digits, maybe followed by any alphanumeric digits.

Magnetically operated control relays Model(s) MR07-S....

Overload relays Model(s) MCOR-1, may be followed by different numbers or SM.

MCOR-2, may be followed by different numbers or G.

MCOR-3, may be followed by different numbers or G.

U12/16, U32, U60

Pilot lights Model(s) PL22-D-#-24, PL22-D-#-S, PL22-TX-#-120, PL22-TX-#-230, PL22-TX-#-400

Push button devices Model(s) B

Suppressor units Model(s) MC-E...

- Where # stands for color of lens (optional), G-green, R-red, Y-yellow, S-blue, W-white, A-amber.

* - Followed by additional letters and/or numbers.

@ - followed by 24, 110, 230 or 400

X - Where X is any character.

Last Updated on 2015-09-23

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

Reprinted from the Online Certifications Directory with permission from UL

© 2015 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2015 UL LLC".